



CVDD 300, 400 SPECIFICATIONS

Model Number	Capacity Range (pF)	Voltage (kV) Peak		Current Amps (RMS) Max.	Type	Nominal Dimensions		Torque (in lbs.) Max.	Direct Pull (lbs.) Max.	Weight (nominal)
		Test	Working			Length (in/mm)	Diam. (in/mm)			
CVDD-300-7.5S	10-300	7.5	4.5	75	Ceramic	7.50 / 191.00	3.40 / 87.40	1.8	29	3 lb.
CVDD-300-10S	10-300	10	6.0	80	Ceramic	7.50 / 191.00	3.40 / 87.40	1.8	29	3 lb.
CVDD-300-15S	10-300	15	9.0	85	Ceramic	7.50 / 191.00	3.40 / 87.40	1.8	29	3 lb.
CVDD-400-7.5S	20-400	7.5	4.5	70	Ceramic	7.50 / 191.00	3.40 / 87.40	2.7	35	3 lb.
CVDD-400-10S	20-400	10	6.0	75	Ceramic	7.50 / 191.00	3.40 / 87.40	2.7	35	3 lb.
CVDD-400-15S	20-400	15	9.0	80	Ceramic	7.50 / 191.00	3.40 / 87.40	2.7	35	3 lb.

NOTES:

Mounting: Use flange FM1H on fixed end. Tapped holes on variable end.

