



**CFHD 12, 18, 25, 50 SPECIFICATIONS**

Model Number	Capacity (pF) ±10%	Voltage (kV) Peak		Current Amps (RMS) Max.	Type	Nominal Dimensions		Weight (nominal)
		Test	Working			Length (in/mm)	Diam. (in/mm)	
CFHD-12-45S	12	45	27	90	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 3 oz.
CFHD-12-50S	12	50	30	95	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 3 oz.
CFHD-12-55S	12	55	33	95	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 3 oz.
CFHD-12-60S†	12	60	36	95	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 3 oz.
CFHD-18-45S	18	45	27	105	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-18-50S	18	50	30	110	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-18-55S	18	55	33	115	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-18-60S†	18	60	36	120	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-25-45S	25	45	27	100	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-25-50S	25	50	30	110	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-25-55S	25	55	33	115	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-25-60S†	25	60	36	120	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 4 oz.
CFHD-50-45S	50	45	27	125	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 5 oz.
CFHD-50-50S	50	50	30	130	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 5 oz.
CFHD-50-55S	50	55	33	135	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 5 oz.
CFHD-50-60S†	50	60	36	140	Ceramic	5.18 / 131.60	2.44 / 62.00	1 lb. 5 oz.

NOTES:

*Mounting:* Ferrule mount both ends. Use FM1H flange.

† Maximum diameter is 2.70 in. with corona rings.

